

Stock Appearing (SA)

Tree Type: 0.400 Pro light

Ladder Type: Pro Ladder

Qualifying: Ranked from quickest to slowest elapsed times in qualifying

Weigh-In: Not Required Staging: Courtesy staging enforced

Deep Staging: Permitted

Race Format: Single-elimination, heads-up racing

Field Size: Up to 32 cars per field

Class Requirements

- Open to the following vehicles:
 - FWD/AWD Eclipse/Talon or Laser (1G or 2G)
 - AWD Galant VR-4 o Evolution VII, VIII, IX, X
 - Genesis Coupe o Stealth/3000 GT Coupe
 - Subaru WRX and WRX Sti
- Vehicles quicker than 10.50-seconds require catch pan or engine diaper

Permitted/Not-Permitted Modifications

- **TURBO:** Mitsubishi's must use a stock bolt pattern turbine inlet and must be positioned in the stock location. FP Zero, Green, Red, Black and HTA DSM86s are legal for the class. FP/TiAL turbine housings using a TiAL external wastegate are allowed. Subaru restrictions to be released before 3/31/2024
- **NITROUS-OXIDE:** Not permitted
- **EXHAUST:** Must exit at rear bumper. Sheet metal O2 housings with recirculating or open dumps are OK. External dumps UNDER vehicle only.
- **INTERCOOLER:** Front-mount intercooler (FMIC) and intercooler pipe upgrades are allowed.
- **BOVs:** Blow-off-valve upgrades are allowed.
- **RADIATOR:** Full-size radiator required
- **OIL SYSTEM:** Factory Type Oil Pump and Wet Sump. No dry sump conversions.
- **INTAKES:** Turbo inlet pipe upgrades and filter upgrades OK
- **INTAKE MANIFOLD:** OEM or aftermarket cast allowed w/ single throttle body
- **INTERIOR:** Vehicle must maintain full factory interior including. OEM headliner, OEM carpet, OEM dash, OEM door panels and OEM center console. Aftermarket steering wheel and shifter OK.
- **WINDOWS/WINDSHIELDS:** Must be OEM glass or pre-cut and formed aftermarket scratch-resistant polycarbonate (i.e. Shield's, OpticArmor, etc.). No homemade "lexan" type replacements allowed. No exposed rivets allowed. Aftermarket scratch-resistant polycarbonate must install in same manner as factory glass and factory-type trim must be employed.
- **MAF:** MAF upgrades allowed. Deletion MAF OK with SD conversion
- **BATTERY:** Battery kits and lithium battery upgrades are allowed.

Stock Appearing (SA)

- SEATS: Racing bucket front seats OK. Both front seats required. If a roll bar, roll cage or harness bar is installed, rear seat delete OK of portion of the seat required to properly mount the bar in place.
- TIRES: DOT Tire Only
- FUEL: Pump gas, race gas, E85 or racing ethanol-fuel blends.