

SFWD16 (SF) Rules 2025

Tree Type: 0.400 Pro light

Ladder Type: Pro Ladder

Qualifying: Each Vehicle Ranked from quickest to slowest elapsed times in qualifying

Weigh-In: Not Required

Staging: Courtesy staging enforced

Deep Staging: Permitted

Race Format: Single-elimination, heads-up racing

Field Size: 16 car ladder

Alternates: It is likely that some of the 16 qualifiers in the SFWD class will be no shows for the first round due to breakage/attrition. The empty spots will be filled by available alternates that make the call to the staging lanes by order of their qualifying position.

Class Requirements

- All vehicles must run an Engine Diaper or catch-pan
- All vehicles must run distilled water only for engine coolant

FWD Vehicles

- Any make or model inline-4 cylinder, inline-5-cylinder or V6 engine permitted

Permitted/Not-Permitted Modifications

- TURBO: Any
- CHASSIS: Factory unibody/frame, no full tube frame vehicles
- FIREWALL: OEM firewall in OEM location (mod for trans tunnel OK)
- SHOCK TOWERS: Front OEM shock towers required. Tube frame in front OK.
- TIRES: Up to 26" in height and 10.5-inch in width
- EXHAUST: Any
- LEXAN: OK
- SEATS: Only driver seat required
- TRANSMISSION: Any
- WHEELIE BARS: None
- FUEL: Race gas, E85, Race Ethanol and Methanol